

## OBRADNI CENTRI

### VERTIKALNI OBRADNI CENTRI



5-OSNI VERTIKALNI OBRADNI CENTRI	MCU 450V(T) -5X	MCU 700V(T) -5X	MCU 1100V(T) -5X
Prečnik radnog stola (mm)	500	630 (800)	1150 x 900 (1200)
Hod (zakretanje) ose A (°)	±120	150 (+30°/-120°)	175° (+45° / -130°)
Hod (zakretanje) ose C (°)	360°	360°	360°
Maks. opterećenje radnog stola (kg)	500 (350)	850 (1300)	2200
Hod po X-osi, Y-osi, Z-osi (mm)	450 x 800 x 400	700 x 820 x 550	1100 x 1550 x 1000
Maks. broj obrtaja glavnog vretena (min <sup>-1</sup> )	12000 / 18000 / 24000	10000 / 12000 / 18000 / 24000	10000 / 12000 / 18000 / 24000
Snaga motora vretena (S1/S6- 40%) (kW)	19/27 (32/48)	20/26	29 / 25 / 19 (59 / 50 / 39)
Nazivni obrtni moment (S1/S6- 40%) (Nm)	60/86 (130/200)	262/340	113 / 100 / 60 (654 / 579 / 451)
Broj mesta u magacinu alata	30 (60)	24	60 [120, 240]



5-OSNI VERTIKALNI OBRADNI CENTRI	MCV 1000 POWER 5AX	MCV 1000 SPEED 5AX	MCV 1000 SPRINT 5AX	MCV 1000 RAPID 5AX
Prečnik radnog stola (mm)	520	520	520	520
Hod (zakretanje) ose A (°)	± 110°	± 110°	± 110°	± 110°
Hod (zakretanje) ose C (°)	360°	360°	360°	360°
Maks. opterećenje radnog stola (kg)	400	400	400	400
Hod po X-osi, Y-osi, Z-osi (mm)	800 x 590 x 480	800 x 590 x 520	800 x 590 x 520	800 x 590 x 520
Maks. broj obrtaja glavnog vretena (min <sup>-1</sup> )	8000	12000	18000	24000
Snaga motora vretena (S1/S6- 40%) (kW)	28 / 43	33 / 48	25 / 35	19 / 26,7
Nazivni obrtni moment (S1/S6- 40%) (Nm)	406 / 623	130 / 200	86 / 120	60 / 86
Broj mesta u magacinu alata	24 (40)	30 (60)	30 (60)	30 (60)

OVE MAŠINE SU U PONUDI I SA TRI OSE