

BUŠILICE

STUBNE BUŠILICE



STUBNE BUŠILICE		VS 25-260 TAURUS	VS 40 SPRINT	VS 40-420/430 CASTOR
Prečnik bušenja u čelik 600 Mpa	(mm)	25	40	40
Dubina bušenja	(mm)	180	220	220
Konus vretena	(Morse)	3	4	4
Prenos		flexible (belt)	mechanical	elastic
Broj stepeni		2	without degrees	12/18
Opseg broja obrtaja vretena	(min ⁻¹)	80 ÷ 2800	45 ÷ 2800	56 ÷ 2800
Pomak		4	manual	4
Opseg pomaka	(mm/obr)	0,08 ÷ 0,32	0,11 ÷ 0,45	0,11 ÷ 0,45
Snaga motora	(kW)	1,1	2,2	2,2 / 2,3

STUBNE BUŠILICE		VS 25-290 SIRIUS	VS 32 HERKULES	VS 32 SATURN
Prečnik bušenja u čelik 600 Mpa	(mm)	25	32	32
Dubina bušenja	(mm)	180	180	180
Konus vretena	(Morse)	3	4	4
Prenos		mechanical	elastic	mechanical
Broj stepeni		2	2	2
Opseg broja obrtaja vretena	(min ⁻¹)	80 ÷ 2800	80 ÷ 2800	80 ÷ 2800
Pomak		4	4	4
Opseg pomaka	(mm/obr)	0,08 ÷ 0,32	0,08 ÷ 0,32	0,08 ÷ 0,32
Snaga motora	(kW)	1,1	1,5	1,5