


# GLODALICE

## HORIZONTALNE GLODALICE



HORIZONTALNE GLODALICE SA POKRETNIM STOLOM I POPREČNO POKRETNIM STUBOM		FUT 150	FUT 150-125	FUT 200	FUT 200-125
Hod po X osi	(mm)	3000 / 4000 / 5000	3000 / 4000 / 5000	3000 / 4000 / 5000	3000 / 4000 / 5000
Hod po Y osi	(mm)	2000 / 2500 / 3000	2000 / 2500 / 3000	2000 / 2500 / 3000	2000 / 2500 / 3000
Hod po Z osi	(mm)	1500	1500	2000	2000
Hod po W osi	(mm)	-	1250 / 1500	-	1250 / 1500
Stezna površina stola	(mm)	1600 × 1800 / 1800 × 2200 / 2000 × 2400	1600 × 1800 / 1800 × 2200 / 2000 × 2400	1600 × 1800 / 1800 × 2200 / 2000 × 2400	1600 × 1800 / 1800 × 2200 / 2000 × 2400
Raspon pomaka po osama X / Y / Z / W	(mm/min)	1 ÷ 20000 (30000)	1 ÷ 20000 (30000)	1 ÷ 20000 (30000)	1 ÷ 20000 (30000)
Snaga glavnog motora	(kW)	30 / 37 / 45	30 / 37 / 45	30 / 37 / 45	30 / 37 / 45

HORIZONTALNE GLODALICE SA FIKSNIM STOLOM I UZDUŽNO POKRETNIM STUBOM		FU(Q)-A	FU(Q)-B
Hod po X osi	(mm)	4000 ÷ 24000 (po 1000)	4000 ÷ 24000 (po 1000)
Hod po Y osi	(mm)	1400 / 2000 / zatim posle 500 do 5000	4000 zatim posle 1000 do 8000
Hod po Z osi	(mm)	1250 / 1500 / 2000	1600 / 2000
Stezna površina stola	(mm)	(opciono)	(opciono)
Raspon pomaka X	(mm/min)	1 ÷ 20000	1 ÷ 15000
Raspon pomaka Y	(mm/min)	1 ÷ 20000	1 ÷ 15000
Raspon pomaka Z	(mm/min)	1 ÷ 20000 / 15000 / 12500	1 ÷ 15000
Raspon pomaka W	(mm/min)	-	1 ÷ 10000
Snaga glavnog motora	(kW)	30 / 37 / 45	60

